

Kanaal Noord 350  
7323 AM Apeldoorn  
The Netherlands  
Phonenumber +31 55 5761693  
Faxnumber +31 55 5761669

E-mail info@shada.nl  
Internet www.shada.nl  
VAT-Number NL818624760B01  
KvK Enschede 0810 0006

BIC / Swift INGBNL2A  
ING Bank USD 02.01.01.570  
IBAN USD NL19INGB0020101570  
ING Bank EUR 67.42.68.628  
IBAN EUR NL39INGB0674268628

## MATERIAL SAFETY DATA SHEET

Date: Jan/8/2014

File No.: PH-W5-878

### 1. Identification of the substance/preparation and of the company/undertaking

Identification of the product

Product name :

Chemical System:

Model:

Designated for RECHARGE?

Lithium Ion Cell

LiCoO<sub>2</sub>/C

Cylindrical Type Cells\_

*K* Yes No

Manufacturer/supplier identification

Company :

Contact for information :

Emergency telephone No. :

Guangzhou Great Power Energy & Technology Co., Ltd.

922 Xicun Section, Shiliang Road, Shawan, Panyu,  
Guangzhou, GD, PRC

0086-20-39196888

### 2. Composition/information on ingredients

Ingredient	Percent	CAS Index No./ECNo.	Molar mass	Molecular formula	Symbol
Lithium cobaltate	28.4%	12190-79-3		LiCoO <sub>2</sub>	
Graphite	17.1%	7782-42-5		C	
Lithium hexafluorophosphate	1.3%	21324-40-3		LiPF <sub>6</sub>	
Ethylene carbonate	3.4%	96-49-1		C <sub>3</sub> H <sub>4</sub> O <sub>3</sub>	
Diethyl carbonate	4.7%	105-58-8		C <sub>5</sub> H <sub>10</sub> O <sub>3</sub>	
Dimethyl carbonate	3.8%	616-38-6		C <sub>3</sub> H <sub>6</sub> O <sub>3</sub>	
Polypropylene	2%	9003-07-0		(C <sub>3</sub> H <sub>6</sub> ) <sub>n</sub>	
Steel	31.1%	7439-89-6		Fe	
Copper	5.7%	7440-50-8		Cu	
Aluminum	2.5%	7429-90-5		Al	

Weight of metallic lithium per cell: Og. There is na metallic lithium in the lithium-ion battery.

The lithium polymer battery is with a Watt-hour rating ~ 20 Wh/Cell (cell), ~ 100 Wh (battery pack).

### 3. Hazards identification

Health Hazards (Acute and Chronic):

For the battery cell, chemical materials are stored in a hermetically sealed can, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, or added electric stress by misuse the cell case will be breached and hazardous materials may be released. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

Carcinogenicity:

NTP: None IARC Monograph: None OSHA Regulated: None

		<b>SHADA</b> international		
Kanaal Noord 350	E-mail	info@shada.nl	BIC / Swift	INGBNL2A
7323 AM Apeldoorn	Internet	www.shada.nl	ING Bank USD	02.01.01.570
The Netherlands	VAT-Number	NL818624760B01	IBAN USD	NL19INGB0020101570
Phonenumber +31 55 5761693	KvK Enschede	0810 0006	ING Bank EUR	67.42.68.628
Faxnumber +31 55 5761669			IBAN EUR	NL39INGB0674268628

#### Medical Conditions Generally Aggravated by Exposure:

An acute exposure will not generally aggravate any medical condition.

Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.

Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and the stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and the stimulation on the eye. Inflammation of the eyes may occur.

Environmental effects:

Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards:

If the electrolyte contacts with water, it may generate detrimental hydrogen fluoride.

Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

#### 4. First aid measures

After inhalation contact:	Make the victim blow his/her nose, gargle. Seek medical attention if necessary.
After skin contact:	Remove contaminated clothes and shoes immediately. Immediately wash extraneous matter or contact region with soap and plenty of water.
After eye contact:	Do not rub eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention.
After ingestion contact:	Make the victim vomit. Immediately seek medical attention.

#### 5. Fire-fighting measures

Extinguishing Media:	Plenty of water, CO <sub>2</sub> gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.
Specific methods of fire-fighting:	When the battery burns with other combustibles simultaneously, take fire extinguishing method which corresponds to the combustibles. Extinguish a fire from the windward as much as possible.
Flammability Limits:	Not available

#### 6. Accidental release measures

The preferred response is to leave the area and allow the batteries to cool and the vapors to dissipate. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

#### 7. Handling and storage

Avoid mechanical or electrical abuse. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

#### 8. Exposure controls/personal protection

Specific control parameter:

Personal protective equipment



Kanaal Noord 350  
7323 AM Apeldoorn  
The Netherlands

Phonenumber +31 55 5761693  
Faxnumber +31 55 5761669

E-mail info@shada.nl  
Internet www.shada.nl  
VAT-Number NL818624760801  
KvK Enschede 0810 0006

BIC / Swift INGBNL2A  
ING Bank USD 02.01.01.570  
IBAN USD NL19INGB0020101570  
ING Bank EUR 67.42.68.628  
IBAN EUR NL39INGB0674268628

Respiratory protection (Specify Type) : Not necessary under conditions of normal use.  
Ventilation: Not necessary under conditions of normal use.  
Protective Gloves: Not necessary under conditions of normal use.  
Eye protection: Not necessary under conditions of normal use.  
Other Protective (Clothing or Equipment): Not necessary under conditions of normal use.

## 9. Physical and chemical properties

### Appearance

Physical state: Solid  
Form: Cylindrical  
Color: Metallic color  
Odor: No odor  
PH: N/A  
Specific temperatures: Temperature ranges changes in physical state occur.  
Flash point: N/A  
Explosion properties: N/A  
Density: N/A  
Solubility: with indication of the solvent(s): Insoluble in water

## 10. Stability and reactivity

Stability: Stable  
Conditions to Avoid: When cell is exposed to an external short-circuit, crushes, deformation, high temperature above 100 degree C, it will cause heat generation and ignition. Avoid direct sunlight and high humidity.  
Hazardous Decomposition or By-products: Acid or harmful gas is emitted during fire.  
Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous polymerization will not occur.

## 11. Toxicological information

Acute toxicity :  
Copper 60-100mg sized coarse particulate causes a gastrointestinal disturbance with nausea and inflammation. TDLo, hypodermie - Rabbit 375mg/kg  
Organic electrolyte LD50, oral - Rat 2,000mg/kg or more

### Further toxicological information :

Aluminum By the long-term inhalation of coarse particulate or fume, it is possible to cause lung damage (aluminum lungs).  
Graphite Long-term inhalation of high levels of graphite coarse particulate may cause lung disease or a tracheal disease.

## 12. Ecological information

Ecotoxic effects : N/A

Further ecological data: N/A



		<b>SHADA</b> international		
Kanaal Noord 350	E-mail	info@shada.nl	BIC / Swift	INGBNL2A
7323 AM Apeldoorn	Internet	www.shada.nl	ING Bank USD	02.01.01.570
The Netherlands	VAT-Number	NL818624760801	IBAN USD	NL19INGB0020101570
Phonenumber +31 55 5761693	KvK Enschede	0810 0006	ING Bank EUR	67.42.68.628
Faxnumber +31 55 5761669			IBAN EUR	NL39INGB0674268628

### 13. Disposal considerations

Great Power encourages battery recycling. Our Li-ion batteries are recyclable through the Rechargeable Battery Recycling Corporation's (RBRC) *Charge Up to Recycle! Program*. For information call 1-800-8-BATTERY or see their website at [www.rbrc.org](http://www.rbrc.org). Li-ion batteries must be handled in accordance with all applicable state and federal laws and regulations.

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212° F. Such treatment can vaporize the liquid electrolyte causing cell rupture. Do not use in combination with fresh and used lithium batteries neither with other type of battery.

### 14. Transport information

International transport regulations :

1. International Air Transport Association (IATA) pursuant to Packing Instruction 965-967, Section II
2. International Maritime Dangerous Goods Code (IMDG) pursuant to Special Provisions A188 and A230.
4. U.S. hazardous materials regulations pursuant to 49 CFR 173.185 and Special Provision A188.

UN-No.: 3480

IATA Packaging Instruction Packing Instruction 965-967 Section TI

Great Power Li-ion cells pass the tests defined in UN model regulation section 38.3. Cells and batteries are packed according to the requirement of 55<sup>th</sup> Edition of the IATA Dangerous Goods Regulations (DGR).

If Great Power Li-ion cells are used to construct battery packs, the assembler of that pack is responsible to ensure the battery has been tested in accordance with the requirements contained in the UN Model Regulations, Manual of Test and Criteria. Part III, subsection 38.3.

### 15. Regulatory information

N/A

### 16. Other information

Make people :	Professional post : R&D Engineer	Name(sign) : James Lee
Make unit:	Name: R&D Department	Phone : 0086-20-39196888
	Address : R&D Dept., Panyu Plant.,	

Date of issue : 201410118

DISCLAIMER : The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Guangzhou Great Power Energy & Technology Co.,Ltd makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.