



<b>Type .....</b>	57656	<b>Safety Features .....</b>	Wrong cell (alkaline) detection Wrong polarity detection (mechanical) Short circuit detection
<b>Designation .....</b>	Mini Charger		
<b>System to charge .....</b>	NiMH (Nickel Metal Hydride)	<b>Housing Material .....</b>	ABS
<b>Cell sizes .....</b>	AA or AAA	<b>Housing colour .....</b>	White/Light Grey
<b>Cell configuration.....</b>	2 cells (pairwise) AA or AAA		
<b>Input .....</b>	100-240V 50-60Hz 3W	<b>Dimensions</b>	<b>Charger:</b>
<b>AC-Plug .....</b>	EU-Plug	Length .....	102.5 ± 1 mm
		Width .....	43 ± 1 mm
		Height .....	63.2 ± 1mm
		Weight .....	64 ± 3g
<b>Charging currents .....</b>	2xAA: 385mA / 2XAAA: 155mA		
<b>Trickle charge current.....</b>	60mA (AA/AAA)		
<b>Cut off Timer .....</b>	8.5h ± 0.2h		
<b>Charge Termination .....</b>	-dV cut off		
<b>Charge Indicator .....</b>	green LED		
charging .....	blinking slow		
defective/wrong cell .....	blinking fast		
charging complete .....	solid green		

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**